





```
pyramid2.cpp
```

A context for demonstrating bulletproof code

COMMAND LINE INPUT



```
int main(int argc, char* argv[])
```





COMMAND LINE INPUT

```
#define HEIGHT 20

int main()
{
    for (int level = 0;
         level < HEIGHT; level++)
        . . .
}
```

```
int main(int argc, char* argv[])
{
    int height = atoi(argv[1]);

    for (int level = 0;
         level < height; level++)
        . . .
}
```



VALIDATING INPUT

- Bulletproof code

- Detects errors
- Displays diagnostics
- Avoids failures

```
if (argc != 2)
{
    cerr << "USAGE: pyramid <height>" << endl;
    exit(1);
}

int height = atoi(argv[1]);
```



VALIDATING INPUT TYPE

```
if (argc != 2)
{
}

for (size_t i = 0; i < strlen(argv[1]); i++)
    if (!isdigit(argv[1][i]))
    {
        cerr << "Invalid integer: " << argv[1] << endl;
        exit(2);
    }

int height = atoi(argv[1]);
```



VALIDATING INPUT BOUNDS

```
int height = atoi(argv[1]);  
  
if (height < 0 || height > 20)  
{  
    cerr << "Height is out of bounds" << endl;  
    exit(3);  
}
```



```
char input[10];

if (argc != 2)
{
    cout << "Please enter the pyramid height: ";
    cin.getline(input, 10);
}
else
    strcpy(input, argv[1]);

for (size_t i = 0; i < strlen(input); i++)
    if (!isdigit(input[i]))
    {
        cerr << "Invalid integer: " << input << endl;
        exit(1);
    }

int height = atoi(input);
```

FLEXIBLE INPUT

COMMAND LINE INPUT TO `string` OBJECTS

```
string input;

if (argc != 2)
{
    cout << "Please enter the pyramid height: ";
    getline(cin, input);
}
else
    input = argv[1];
    . . .
int height = stoi(input);
```